


Charleston Harbor



Channel Center
 Federal Channel
 Disposal Area

Depth FT MLLW

-5.3 - 30
30.1 - 32.5
32.6 - 35
35.1 - 37.5
37.6 - 40
40.1 - 42.5
42.6 - 45
45.1 - 47
47.1 - 49
49.1 - 80.4



Notes:

- Soundings are expressed in positive feet and tenths and are referenced the Mean Lower Low Water (MLLW) datum.
- Project surveyed with USACE survey vessels equipped with GPS positioning and hydrographic survey equipment that meets USACE Navigation and Dredging standards for soft bottom hydrographic surveys.
- Soundings are calibrated to tide gauges that are set to MLLW and referenced to published benchmarks.
- Horizontal Datum: State Plane NAD-83 SC-3900 Intl Feet
- Project was designed by the Charleston District of the U.S. Army Corps of Engineers. The initials or signatures and registration designations of individuals appear on these project documents within the scope of their employment by ER 1110-1-8152.
- Maps and associated information represents the result of surveys made on the date indicated and can only be considered as indicating the general condition existing at that time. These conditions are subject to rapid change due to shoaling events. A prudent mariner should not rely exclusively on the information provided here.
- Aids to Navigation obtained from the U.S. Coast Guard Light List.



Survey Dates:

- Charleston Upper Harbor - Feb 2014
- Charleston Lower Harbor - March 2014
- Shipyards River - March 2014
- Anchorage Basin - March 2014
- Ashley River - March 2013